## Polycom® SoundStation® IP 3000 — 3Com® NBX®

Voice over IP (VoIP) conferencing for NBX networked telephony solutions

### Highlights

**Acoustic Clarity Technology** – Allows simultaneous natural conversation – the industry's best full duplex

**Fully compatible** — Works seamlessly with SuperStack® 3 NBX and NBX 100 Networked Telephony Solutions

**Investment protection** — Downloadable upgrades as standards develop and protocols evolve

**360-degree room coverage** – A powerful, digitally-tuned custom speaker and three sensitive microphones provide uniform coverage of a small to medium-sized conference room or office

**Easy-to-install and use** – Plug into your NBX system and start conferencing in minutes\*

\*3Com license required. Sold separately

# With the SoundStation IP 3000, the promise of single-network communications is now a reality in the conference room.

There is no need for special analog lines and/or analog terminal adapters. Simply plug the SoundStation IP 3000 - 3Com NBX into your Ethernet network, and you're ready for the next conference call.

Whether you are conferencing with colleagues down the block or customers around the world, the SoundStation IP 3000 - 3Com NBX offers NBX users the same Acoustic Clarity Technology that has made Polycom the leader in voice conferencing for IP-enabled telephone systems. Start having more efficient and more productive meetings with the SoundStation IP 3000 - 3Com NBX.

### The best-in-class choice for The Polycom Office™

With integrated video, voice, data, and Web capabilities, The Polycom Office is the only solution that offers you an easy way to connect, conference, and collaborate any way you want. The Polycom Office is our commitment to making distance communications as natural and interactive as being there. Work faster, smarter, and better with the SoundStation IP 3000 - 3Com NBX and The Polycom Office.



### Polycom SoundStation IP 3000 - 3Com NBX Specifications

#### **Technical specifications**

#### Size

 14.5 in x 12.25 in x 2.5 in (36.8 cm x 31.1 cm x 6.4 cm) (W x H x D)

#### Weight

• 1.75 lb. (0.8 kg)

#### Power

 Universal power supply (110/220 V, 50/60 cycles) (100 V for Japan).

#### Display

- High-resolution graphical LCD
- Keypad
  - 12-key telephone keypad
  - On-hook/off-hook, redial, mute, volume up/down keys, menu navigation keys
  - Three context-dependent softkeys

#### Loudspeaker

- Frequency response: 300 3300 Hz
- Volume: 85 dB volume (peak) at 0.5 meters

#### **Network interface**

• Ethernet 10/100BaseT

#### **Regulatory compliance**

#### Safety

- UL1950
- CSA C22.2, No. 950
- EN60950
- IEC60950
- AS/NZS3260

#### • FMC

- FCC (47 CFR Part 15) Class B
- ICES-003 Class
- EN55022 Class B
- CISPR22 Class B
- AS/NZS 3548 Class B
- VCCI Class B
- EN50224

#### SoundStation IP 3000 - 3Com NBX ships with:

- Quick reference guide
- User manual
- Warranty registration card
- Tabletop console with integrated display and keypad
- Power Interface Module (PIM)
- Universal power supply brick
- 6 ft Cat 5 Ethernet cable
- 25 ft Power/Ethernet cable (Connects PIM to console)

#### Warranty

One year

#### **Environment conditions**

- Operating temperature: 32° 104° F (0° 40° C)
- Relative humidity: 20% 85% (noncondensing)
- Storage temperature: -22° 131° F (-30° 55° C)

#### Part number

• 2200-06632-001

North American part number only.

Please call for more information on international products.

©2003 Polycom, Inc. All rights reserved.

Polycom, the Polycom logo and SoundStation IP are registered trademarks and The Polycom Office is a trademark of Polycom, Inc. in the U.S. and various countries. All other trademarks are the property of their respective companies.

Specifications subject to change without notice.



4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only. For North America, Latin America and Caribbean (T) +1.925.924.6000, (F) +1.925.924.6100

**Polycom EMEA:** 270 Bath Road, Slough, Berkshire SL1 4DX, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010

Polycom Hong Kong Ltd.: Polycom Hong Kong Ltd., Rm 1101 MassMutual Tower, 38 Gloucester Road, Wanchai, Hong Kong, (T) +852.2861.3113, (F)+852.2866.8028

Part No. 3726-07255-001 Rev. 05/03