

# EtherFast<sup>®</sup> Cable/DSL Router

*Connect Your Network to Your High-Speed Cable or DSL Internet Pipeline with the Ultimate in Security and Control*

Share Your Broadband Connection



Instant Broadband Cable/DSL Router  
(BEFSR41)

## Benefits

- Build a Broadband Network in Your Home or Small Office
- Equipped with a 4-Port EtherFast Switch
- Access the Internet Over Your Entire Network with Only One IP Address
- Create a Firewall to Protect Your PCs From Outside Intruders
- Dramatically Speed Up Your Gaming and Multimedia Connections
- Free Technical Support - 24 Hours a Day, 7 Days a Week
- Full 1-Year Warranty

## Features

- Connects to a Broadband Modem or an Ethernet Backbone
- Equipped with an Internal 4-Port 10/100 Switch
- Use Just one IP Address to Access the Internet Over Your Entire Network
- Creates a Firewall to Protect Your PCs From Unwanted Outside Intruders
- Configurable Through Any Networked PC's Web Browser
- Internal 4 -Port Switch Dramatically Speeds Up Your Gaming and Multimedia Connections
- Able to Act as Either a DHCP Server or Client
- Compatible with All Standard Internet Applications
- Administrators Can Block Specific Internal Users' Internet Access
- Technical Support - 24 Hours a Day, 7 Days a Week
- Full 1-Year Warranty

## Specifications

<b>Standards</b>	IEEE 802.3, IEEE 802.3u
<b>Protocol</b>	CSMA/CD
<b>Ports</b>	4 10BaseT/100BaseTX RJ-45 Ports One 10BaseT Broadband (WAN) Uplink Port
<b>Cabling Type</b>	<b>10BaseT:</b> UTP/STP Category 3 or 5 <b>100BaseTX:</b> UTP/STP Category 5 or Better
<b>Topology</b>	Star
<b>Speed</b>	WAN Router: 10Mbps (10BaseT Ethernet) LAN: 10Mbps (10BaseT Ethernet) or 100Mbps (100BaseTX Fast Ethernet)
<b>LEDs</b>	Power, Ready/Test, Link and Activity for both WAN and LAN port(s), Partition and Collision for LAN ports

## Package Contents

### Instant Broadband Cable/DSL Router

- One Instant Broadband Cable/DSL Router
- One AC Adapter and Power Cord
- User Guide and Registration Card

(Model No.: BEFSR41)

## Environmental

<b>Dimensions</b>	5.6" x 9.3" x 1.8"
<b>Unit Weight</b>	12 oz.
<b>Power</b>	Output: External, 5V DC, 3A Input: 100-240VAC 1A 50/60HZ
<b>Certifications</b>	FCC Class B CE Mark, Commercial UL and CSA Listed
<b>Operating Temp.</b>	0°C to 40°C (32°F to 104°F)
<b>Storage Temp.</b>	-20°C to 70°C (-4°F to 158°F)
<b>Operating Hum.</b>	10% to 85% Non-Condensing
<b>Storage Hum.</b>	5% to 90% Non-Condensing

<b>Sales</b>	<b>(800) 546-5797</b>
<b>Support</b>	<b>(800) 326-7114</b>
<b>Fax</b>	<b>(949) 261-8868</b>
<b>Email</b>	<b>sales@linksys.com</b>
<b>Web</b>	<b>www.linksys.com</b>

